

QUICK SPECS

Weight	12,633 lbs	
Horsepower	111.5 HP	
Max Payload	8,379 lbs	

Built for the toughest jobsites on Earth.



Dump trucks are great, if they can get to the jobsite. But low ceilings, swampy or soft ground, snow and steep slopes can be obstacles to getting a job done. Not with the C50R. This durable, rubber-tracked, high-flotation, all-terrain carrier is right at home in conditions where others can't operate. Even in places where it's impossible or dangerous to turn, the seat and travel levers turn 180 degrees together so you're always moving forward. Take a seat. You'll quickly see that conditions don't decide whether a job gets done; only you do.

INNOVATIVE FEATURES



Neat, Easy Dumping For Tougher Conditions

With an ample 65-degree dumping angle and extended 2ft-2in distance from the dumping platform to the ground, you always get a sure and neat soil discharge with just a single dumping stroke. For even more versatility, add an optional 180-degree swivel dump loading platform for safe, efficient sideways dumping.



Reversible Seat and Travel Lever

The operator's seat and travel levers turn 180 degrees so the operator is always moving forward. This provides a safer work environment on mountain paths and other turn-restricted worksites. It also reduces damage to environmentally sensitive areas because there's no need to make skid turns.



Safe, Comfortable Cab

The operator's area is spacious and built for comfort. The C50 has been engineered for enhanced panoramic visibility from the operator's seat. The powerful 111.5 HP engine is also built for clean exhaust and quiet operation. Add an optional enclosed cab with heat and AC for year-round comfort.

C50R-5

POWERFUL, EFFICIENT WATER-COOLED, 4-CYLINDER 111.5 HP TIER 4 FINAL DIESEL ENGINE

AUTOMATIC 2-SPEED HYDROSTATIC TRANSMISSION

TOUGH UNDERCARRIAGE FOR EXTREME CONDITIONS

IDEAL FOR STEEP SLOPES, SAND, SNOW & SWAMPY CONDITIONS

OPTIONAL ENCLOSED CAB WITH HEAT & A/C

OPTIONAL BARE-TYPE BED (NO DUMP BODY OR DUMP CYLINDER)

LARGE PLATFORM
AND SUFFICIENT
PTO TO SERVE AS
MOUNTING VEHICLE
FOR MULTIPLE
ATTACHMENTS





C50R-5

Dimensions - C50R-5


THREE-WAY DUMP VESSEL

H. 6' 1"





SWIVEL DUMP VESSEL



Model				C50R-5	C50R-5
Dump vessel type				One-way dump type	Swivel-dump type
Shape of Vessel				Box-shape	V shape
Operating Weight	Net, unloaded		lbs (kg)	12,633 (5,730)	13,360 (6,060)
Engine	Туре		-	Direct Injection Combustion Water-cooled 4-cyl. Diesel	
	Model		-	YANMAR 4TNV94FHT-NTBC	
	Output		HP (kW)	111.5 / 83.1	
Transmission -				Variable Speed 2 Pump, 2 Motor Hydrostatic (HST)	
Undercarriage	Track Type	-		Steel-Reinforced Rubber Track	
	Track Width		ft-in (mm)	1'6" (450)	
	Min. Ground Clearance		ft-in (mm)	1′5" (435)	
	Ground Contact Pressure	w/o load	PSI (kPa)	3.4 (23.5)	3.6 (24.9)
		w/ load	PSI (kPa)	5.7 (39.5)	5.7 (39.5)
Performance	Max. Payload		lbs (kg)	8,379 (3,800)	7,718 (3,500)
	Max. Dumping Angle		degrees	65°	65°
	Dump Clearance		ft-in (mm)	2'2" (660)	2'11" (890)
	Dump Body Capacity	Struck	yd³ (m³)	1.8 (1.4)	1.6 (1.2)
	Max. Travel Speed		mph (km/h)	5.9 (9.5)	5.9 (9.5)